

584e CRD5



ArmaTrac[®]

www.armatrac.com



ECAPRA ENGINE

ERKUNT'S DOMESTIC PRODUCTION ENGINE BRAND

ENGINE

Normal Mode - Boost Mode [Max. HP / kW]	57 - 63 HP / 41.9 - 46.3 kW
Engine Type	HCE STAGE-V [ECAPRA]
Engine Speed to Achieve Maximum Torque	1400 rpm
Rated Speed in RPM	2200 rpm
Normal Mode - Boost Mode Max. Torque [Nm]	251 - 280 Nm
Emission Level	Stage V
Cylinder Nb. / Aspiration	3 / Turbo Intercooler
Cylinder Volume [Liter]	2.98 LT
Fuel Tank [Liter]	70 Liter
Fuel Injection System	CommonRail Injection

TRANSMISSION

Transmission Type	Carraro Mechanical
Gear Box 4WD	8F-8R
Gear box 4WD Optional	12F-12R
Auto front differential lock [4WD models]	Mechanic
Rear Differential Lock 2WD - 4WD	Mechanic
4wd Remote System	Mechanic
Min - Max Speed [km/h]	1,99-29 [8x8] km/hr 0,43-28.82 [12x12] km/hr

HYDRAULIC SYSTEM

Hydraulic Control Type	Mechanic
Automatic Lifting System	Standard
Hydrolic Power Output	4 units
Hydraulic Pressure [Bar]	190 Bar
Max. Hydraulic Lift Capacity	2200 Kg

PTO

Type	Independent 2V
PTO Speed Synchronized with Wheel Speed	Optional
PTO Speed	540, 540E rpm

MEASURES

Wheelbase 2WD-4WD	2000 - 2064 mm
Total Length 2WD-4WD	3711 mm
Width	1735 mm
Max. Height in Platform 2WD-4WD	2443 mm
Max. Height in Cabin 2WD-4WD	2420 mm
Front track width 2WD-4WD	1300 - 1700 / 1400 - 1800 mm
Rear track width 2WD-4WD	1400 - 1800 mm

WEIGHTS

Total Tractor Weight [4WD, W/O Additional Weights, Canopy]	2900 Kg
Total Tractor Weight [4WD, W/O Additional Weights, Cabin]	3160 Kg
Total Front Weights 2WD-4WD	4 x 20 / 6 x 20 Kg
Total Rear Weights 2WD-4WD	2 x 50 Kg

STANDARD TYRE MEASURES

1st Option - Front 2WD	6,50-16
1st Option - Rear 2WD	13,6-28
1st Option - Front 4WD	280/70/R18
1st Option - Rear 4WD	13,6-28
2nd Option - Front 4WD	260/70/R20
2nd Option - Rear 4WD	340/85/R24
3rd Option - Front 4WD	9,50-R20
3rd Option - Rear 4WD	340/85/R28
4th Option - Front 4WD	-
4th Option - Rear 4WD	-

OPTIONAL

Cabin	Optional
4WD System	Optional